



TIME was founded in 1965 and is considered an industry pioneer. In 1976, the company was bought by O'Flaherty Holdings Limited, Dublin, Ireland.

Versalift® lifts are the result of continual engineering development and market studies. **TIME** Manufacturing Company has the goal of producing models with the characteristics that fill the market's needs in a heavily competitive industry.

Versalift® meets ANSI standards and is CE approved, and we are certified according to ISO 9001 and ISO 14001 standards. Commitment to quality, de-

sign, construction and customer service are keywords for **TIME** Manufacturing Company.

Versalift® lifts are among the world's most sold truck-mounted lifts with working heights from 9 m - 35 m, "live-line"-insulated and low-voltage insulated. Versalift® lifts are the world's most sold van-mounted aerial work platform.

Since 1965, Versalift has produced and sold more than 90,000 Versalifts the world over. Yearly production is appx. 4000 lifts, and lifts have been sold in more than 150 countries. The Versalift division has more

than 400 employees at the factory in Waco. Condor® lifts are truck-mounted lifts from 27 m - 65 m, which are AUS-insulated up to 750 KV.

Condor® was produced by Calavar in California until 1991, when O'Flaherty Holding bought the company and moved production to **TIME** Manufacturing Company in Waco, Texas.

TIME International is the export division of Time Manufacturing Company. The division is located in Farsø, Denmark and deals with the export of more than 1000 lifts yearly to countries outside of North,

Central, and South America. This export is based on a worldwide network of dealerships, which sell with reference to the export division in Denmark.

TIME Danmark, which is located the same place as Time International in Farsø, builds more than 100 lifts yearly on chassis and vans for, among others, the Scandinavian countries, Germany, Holland and Belgium. These are primarily workshop furnished, fully equipped, turn-key lift vehicles for delivery to the energy sector.

Versalift® is known as a reliable, high quality product with low maintenance costs.

Access To Work Green

- ZERO EMISSION, 100% ELECTRICAL
- LOW EMISSION, HYBRID
- LOW EMISSION, NGT



INTERNATIONAL A/S
SØNDERVANG 3 · DK-9640 FARSØ
PHONE: +45 9863 2433 · FAX: +45 9863 2483
SALES@TIMEINTL.DK · WWW.TIMEINTL.DK

MANUFACTURING COMPANY
7601 IMPERIAL DRIVE
WACO 76702-0368 · TEXAS · USA
PHONE: 1 254 399 2100 · FAX: 1 254 399 2650
WWW.TIMEMFG.COM



Access To Work Green

ZERO EMISSION, 100% ELECTRICAL



100% Electrical	ET-32-LE	ET-32-LFXS	ET-36-LF
Working height	11.8 m	11.0 m	12.4 m
Platform height	9.8 m	9.0 m	10.4 m
Max. outreach	6.7 / 5.8 m	6.6 m	6.8 m
Max platform capacity	120 / 200 kg	120 kg	200 kg
Flyboom	Fixed	180° LD	110°
Vehicle brand	Peugeot Boxer L3 H3	Ford Transit	Ford Transit
Min. GVW	4.200 kg	3.500 kg	4.600 kg
Wheel base	4.030 mm	3.500 mm	3.955 mm

Access To Work Green

LOW EMISSION, Hybrid and Natural Gas Technology NGT



Hybrid	ET-30-LE	ET-38-LF	VST-237-LF
Working height	11.2 m	14.2 m	15.0 m
Platform height	9.2 m	12.2 m	13.0 m
Max. outreach	6.7 / 5.8 m	7.3 m	9.0 / 8.4 m
Max platform capacity	120 / 200 kg	200 kg	200 / 265 kg
Flyboom	Fixed	180° LD	180° HD
Vehicle brand	Peugeot Boxer L2 H2	Mercedes Sprinter	MAN
Min. GVW	3.500 kg	5.000 kg	12.000 kg
Wheel base	3.450 mm	3.665 mm	3.050 mm



100% Electrical	VST-237-LF	ET-40-LFHD	VT-54-LF
Working height	15.0 m	15.0 m	18.0 m
Platform height	13.0 m	13.0 m	16.0 m
Max. outreach	9.0 / 8.4 m	9.0 / 8.0 m	11.0 / 9.5 m
Max platform capacity	200 / 265 kg	200 / 265 kg	120 / 200 kg
Flyboom	180° LD	180° LD	180° LD
Vehicle brand	Smith Newton	Smith Newton	Smith Newton
Min. GVW	10.000 kg	7.500 kg	12.000 kg
Wheel base	3.900 mm	3.900 mm	3.900 mm



Hybrid / NGT	VT-54-LF	ET-36-LF	ET-38-LF
Working height	18.0 m	13.7 m	14.2 m
Platform height	16.0 m	11.7 m	12.2 m
Max. outreach	11.0 / 9.5 m	7.7 / 6.7 m	6.6 m
Max platform capacity	200 / 265 kg	120 / 200 kg	200 kg
Flyboom	180° LD	180° LD	180° LD
Vehicle brand	Mercedes Atego	Iveco Daily 50 C 11 NGT	Mercedes Sprinter 516 NGT
Min. GVW	12.000 kg	5.200 kg	5.000 kg
Wheel base	3.560 mm	3.300 mm	4.325 mm